


## EQUIPMENT SPECIFICATIONS

INTERNAL MEASUREMENTS	DOOR OPENING	EQUIPMENT	CUBIC CAPACITY	MAX PAYLOAD	WEIGHT
 <p><b>20 ft STANDARD</b></p>					
Length 5,898 mm 19'4"					
Width 2,352 mm 7'9"	Width 2,340 mm 7'8"		33.2 M <sup>3</sup>	28,180 kg	2,300 kg
Height 2,393 mm 7'10"	Height 2,280 mm 7'6"		1172 ft <sup>3</sup>	62,130 lb	5,070 lb
 <p><b>40 ft STANDARD</b></p>					
Length 12,032 mm 39'6"					
Width 2,352 mm 7'9"	Width 2,340 mm 7'8"		67.7 M <sup>3</sup>	28.750 kg	3,750 kg
Height 2.393 mm 8'10"	Height 2,280 mm 7'6"		2,390 ft <sup>3</sup>	63,385 lb	8,265 lb
 <p><b>40 ft HIGH CUBE</b></p>					
Length 12,032 mm 39'6"					
Width 2,352 mm 7'9"	Width 2,340 mm 7'8"		76.4 M <sup>3</sup>	28.560 kg	3,940 kg
Height 2.698 mm 8'10"	Height 2,585 mm 8'6"		2,700 ft <sup>3</sup>	62,.965 lb	8,685 lb
 <p><b>45 ft HIGH CUBE</b></p>					
Length 13,556 mm 44'6"					
Width 2,352 mm 7'9"	Width 2,340 mm 7'8"		86.4 M <sup>3</sup>	27,860 kg	4,820 kg
Height 2.698 mm 8'10"	Height 2,585 mm 8'6"		3,045 ft <sup>3</sup>	61,025 lb	10,625 lb
 <p><b>REFRIGERATED 40 ft HIGH CUBE</b></p>					
Length 11,571 mm 37'11"					

# HSL - Equipment Specs

Width 2,268 mm 7'5"	Width 2,276 mm 7'5"		67 M <sup>3</sup>	29,150 kg	4,850 kg
Height 2,553 mm 8'4"	Height 2,501 mm 8'2"		2,366 ft <sup>3</sup>	64,270 lb	10,690 lb
 <p><b>OPEN TOP 40 ft</b></p>					
Length 5,889 mm 19'4"					
Width 2,345 mm 7'9"	Width 2,300 mm 7'8"		32.4 M <sup>3</sup>	28,120 kg	2,360 kg
Height 2,346 mm 7'9"	Height 2,215 mm 7'6"		1,144 ft <sup>3</sup>	67,200 lb	5,200 lb